



# **ALPHA® SN100**

# **Pure Tin Solder Alloy**

## **DESCRIPTION**

**ALPHA Sn100** Pure Tin Solder Alloy is suitable for lead tinning, electronic plating, wave soldering and other applications for electronic assemblers interested in instituting a lead-free process. It is also suitable for replenishing the solder loss in Lead-Free solder pot to control / maintain the copper content when necessary. As with all Alpha Bar Solders, Alpha's proprietary alloying process is used to remove certain impurities, particularly oxides.

Alpha's proprietary process is a highly effective method for removing included oxides from solder. This is extremely important because included oxides generate excessive drossing and increase the viscosity of the solder. Solder with higher viscosity can result in increased soldering defects (i.e., solder bridging).

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

### PRODUCT INFORMATION

0.10% of Pb complies with the requirement of RoHS Directive (Article 4.1 of the European Directive 2011/65/EU). Alloy specification for maximum Lead (Pb) Content = 0.05%

Element	Specification%	Element	Specification%
Sn	Balance	Cd	0.002 max
Sb	0.05 max	Zn	0.001 max
Cu	0.05 max	Fe	0.010 max
As	0.03 max	Pb	0.050 max
Ag	0.015 max	Al	0.001 max
Bi	0.050 max	In	0.10 max
Ni	0.010 max	Au	0.002 max



# **TECHNICAL DATA SHEET**

## **TECHNICAL DATA**

Item	Typical Values	
Melting Point (°C)	232	
Density (g/cm³)	7.29	
Thermal Conductivity (W/mK)	73	
Electrical Resistivity (μΩ-m)	0.124	
Tensile Strength (kgf/cm²)	135	

## **AVAILABILITY**

ALPHA Sn100 is available in 1kg (2.2lb) Bar, Chunks, Feeder Ingots and Autofeed Wire.

## **RECYCLING SERVICES**

We provide safe and efficient recycling services to help companies meet their environmental and legislative requirements and at the same time, maximize the value of their waste streams. Our service collects solder dross, solder scrap, and various forms of solder paste waste. Please contact your local sales representative for recycling capabilities in your area.





## **TECHNICAL DATA SHEET**

### **SAFETY & WARNING**

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.** 

### **STORAGE**

Store the solder bar in a cool, dry and non-corrosive environment. Wrap up the solder bar when not in use to reduce exposure to environment.

## **CONTACT INFORMATION**

#### www.macdermidalpha.com

North America 140 Centennial Avenue Piscataway, NJ 08854 1.800.367.5460 **Europe**Unit 2, Genesis Business Park
Albert Drive
Woking, Surrey, GU21 5RW, UK
44.01483.758400

Asia 8/F., Two Sky Parc 51 Hung To Road Kwun Tong, Kowloon, Hong Kong, SAR China

852.2500.5365

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY. WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indicental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.

